

RECEIVED
CENTRAL FAX CENTER

JUL 05 2006

Applicant : Stephen C. Wolf
Serial No. : 10/796,917
Page : 2

IN THE CLAIMS:

Please amend claims 13, 28-30, 33, and 34 as follows:

1. (previously presented) A paddle diverter assembly comprising:
an arm; and
an actuator for moving said arm from a home position to a diverting position,
said actuator being adapted to permit said arm to move away from the diverting position upon
impact with an object to be diverted to thereby absorb at least some of the impact between the
arm and the object being diverted and adapted to return said arm to said diverting position by
an electromagnetic field.
2. (cancelled)
3. (original) The paddle diverter assembly according to Claim 1, wherein said arm
comprises a driven diverting surface.
4. (original) The paddle diverter assembly according to Claim 3, wherein said driven
diverting surface comprises a drive belt.
5. (original) The paddle diverter assembly according to Claim 1, wherein said actuator
extends downwardly from said arm no more than 12 inches.
6. (original) The paddle diverter assembly according to Claim 1, wherein said actuator
comprises a motor and a servo controller selectively powering said motor, said motor
permitting said arm to move away from the diverting position upon impact with the object
and forming an electric spring.
7. (original) The paddle diverter assembly according to Claim 1, wherein said arm includes
a spring, said spring deflecting to absorb impact when said arm impacts the object being
diverted by said arm.
8. (original) The paddle diverter assembly according to Claim 7, wherein said spring
comprises a plate spring.

Applicant : Stephen C. Wolf
Serial No. : 10/796,917
Page : 3

9. (original) The paddle diverter assembly according to Claim 8, wherein said arm includes a medial portion, and said spring being provided at said medial portion.

10. (original) The paddle diverter assembly according to Claim 9, wherein said plate spring includes a longitudinal extent, said arm having a longitudinal axis, said longitudinal extent extending along said longitudinal axis.

11. (original) The paddle diverter assembly according to Claim 10, wherein said arm comprises a driven diverting surface.

12. (original) The paddle diverter assembly according to Claim 11, wherein said driven diverting surface comprises a driven belt.

13. (currently amended) A paddle diverter assembly comprising:

an arm, said arm comprising a driven diverting surface, said driven diverting surface comprising a drive[[n]] belt;

an actuator for moving said arm from a home position to a diverting position, said actuator being adapted to permit said arm to move away from the diverting position upon impact with an object to be diverted to thereby absorb at least some of the impact between the arm and the object being diverted;

wherein said arm includes a spring, said spring deflecting to absorb impact when said arm impacts the object being diverted by said arm, said spring comprising a plate spring;

said arm including a medial portion and a longitudinal axis, and said spring being provided at said medial portion and having a longitudinal extent, said longitudinal extent extending along said longitudinal axis of said arm; and

wherein said plate spring includes a longitudinal groove extending along said longitudinal extent, said drive belt having a rib, said rib extending into said groove wherein said groove provides vertical support to said drive belt.

14. (original) The paddle driver assembly according to Claim 4, wherein said arm supports belt pulleys for supporting said drive belt.

Applicant : Stephen C. Wolf
Serial No. : 10/796,917
Page : 4

15. (previously presented) A paddle diverter assembly comprising:

an arm, said arm comprising a driven diverting surface, and said driven diverting surface comprising a drive belt, said arm supporting belt pulleys for supporting said drive belt;

an actuator for moving said arm from a home position to a diverting position, said actuator being adapted to permit said arm to move away from the diverting position upon impact with an object to be diverted to thereby absorb at least some of the impact between the arm and the object being diverted; and

wherein said arm comprises at least first and second arm portions, said first and second arm portions releasably interlocked, when released said first and second arm portions permitting removal of the drive belt without disassembly of the paddle diverter assembly.

16. (original) The paddle diverter assembly according to Claim 15, wherein said first and second arm portions are slidably releasable.

17. (original) The paddle diverter assembly according to Claim 15, wherein said first and second arm portions include a slidable joint therebetween, said slidable joint being selectively fixable wherein said first and second arm portions are interlocked and being selectively releasable to permit removal of said belt.

18. (original) The paddle diverter assembly according to Claim 17, wherein said slidable joint comprises a dovetail joint.

19. (original) The paddle diverter assembly according to Claim 18, wherein said dovetail joint comprises an angled dovetail joint.

20. (original) The paddle diverter assembly according to Claim 18, wherein said arm portion comprises at least two extruded sections.

21. (previously presented) A diverter system comprising:

a conveying surface having a conveying direction and for conveying an article at a conveying speed;

Applicant : Stephen C. Wolf
Serial No. : 10/796,917
Page : 5

a pair of diverter assemblies at opposite sides of said conveying surface, each of said diverter assemblies comprising an arm mounted for pivotal movement between a non-diverting position and a diverting position wherein said arm is pivoted across at least a portion of said conveying surface; and

a drive system independently and selectively moving said arms between said diverting positions and said non-diverting positions wherein said arms may be individually moved to their respective diverting positions and wherein an article conveyed on said conveying surface is diverted in a diverting direction when the article contacts one of said arms when said one arm is in said diverting position, wherein said drive system permits said arms to pivot away from their diverting positions when impacted by an article to thereby reduce the impact on the article being diverted and return said arms to their diverting positions by an electromagnetic field.

22. (cancelled)

23. (original) The diverter assembly in Claim 21, wherein said drive system comprises a driver for each arm, said drivers being independently actuated to move said arms to their respective diverting positions.

24. (original) The diverter assembly in Claim 23, wherein said drive system comprises a controller, said controller selectively and independently actuating said drivers.

25. (original) The diverter assembly in Claim 24, wherein said controller comprises a servo controller.

26. (original) The diverter assembly according to Claim 21, wherein each of said arms includes a driven diverting surface.

27. (original) The diverter system according to Claim 26, wherein at least one of said driven diverting surfaces comprises a drive belt.

28. (currently amended) The diverter system according to Claim 27, wherein each arm comprises a horizontal extent, said ~~drive at least one driven diverting surface comprising a~~

Applicant : Stephen C. Wolf
Serial No. : 10/796,917
Page : 6

belt extending around said horizontal extent, said belt being driven about said horizontal extent and providing said driven diverting surface.

29. (currently amended) The diverter system according to Claim 21, wherein each of said arms includes a horizontal extent and a belt extending around said horizontal extent, said belts being driven around ~~their~~ the respective horizontal extents and providing driven diverting surfaces for each of said arms.

30. (currently amended) The diverter system according to Claim ~~[[28]]~~ 29, wherein each of said drive belts is driven by a driven roller, said driven rollers driven by said drive system.

31. (original) The diverter system according to Claim 30, wherein each of said driven rollers includes a driven axis about which said driven roller is driven, and said arms pivoting about a respective pivot axis when pivoting between said non-diverting position and said diverting position.

32. (original) The diverter system according to Claim 31, wherein said driven axis of a respective arm and said respective pivot axis of said respective arm are generally collinear.

33. (currently amended) The diverter system according to Claim 32, wherein said drive system is adapted to de-couple movement of said drive belts about said driven axes from movement of said arms about said pivot axes.

34. (currently amended) The diverter system according to Claim 33, wherein said drive system includes a motor for pivoting each of said arms and a motor for driving each of said drive~~[[n]]~~ belts, said motors independently actuated by said drive system.

35-39. (cancelled)

40. (previously presented) A method of selectively diverting an object, said method comprising:

- providing at least one paddle assembly having an arm;
- moving the arm with a drive assembly to a diverting position; and

Applicant : Stephen C. Wolf
Serial No. : 10/796,917
Page : 7

absorbing at least some of the impact between the object and the arm with the drive assembly allowing the arm to move away from the diverting position when the arm makes contact with an object to thereby absorb some of the impact; and
returning the arm to the diverting position with an electromagnetic field.

41. (original) The method according to Claim 40, wherein said moving comprises pivoting the arm to the diverting position.

42. (original) The method according to Claim 41, wherein said pivoting includes pivoting the arm with a servo controlled motor.

43. (original) The method according to Claim 40, further comprising providing a pair of paddle assemblies and selectively moving each of the paddle assemblies to a diverting position.

44. (original) The method according to Claim 43, wherein said selectively includes individually moving the paddle assemblies.

45. (previously presented) The paddle diverter assembly according to Claim 15, wherein said first and second arm portions releasably interlock at a fixed length to form a rigid member having a longitudinal extent along a longitudinal axis and a transverse extent, further comprising first and second spaced apart pulleys mounted to said rigid member, said belt drive being supported by said pulleys about said rigid member, and said first and second arm portions releasably interlocked at a fixed length and being releasable wherein said first pulley and said second pulley can be moved closer together wherein said belt can be removed for repair or replacement.

46. (previously presented) The paddle diverter assembly according to Claim 6, wherein said arm comprises a first arm, said diverter assembly in combination with a conveying surface and a second arm on an opposed side of said conveying surface from said first arm, and a control system, said control system including said servo controller and a second motor for moving said second arm from a home position to a diverting position, and said control system operable to move said first arm and said second arm asynchronously.

Applicant : Stephen C. Wolf
Serial No. : 10/796,917
Page : 8

47. (previously presented) The paddle diverter assembly according to Claim 46, wherein said control system further includes a pair of sensors, said sensors for detecting the leading edge and the trailing edge of an article on said conveying surface, and said control system determining the length of an article being diverted.

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record.

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.